

✓ Appendix 2
Pending Claims

1. (Amended) A printer, comprising:
an image processing means for,
storing a plurality of gamma data in an updateable table, each of the
plurality of gamma data being different from each other in a value on which a
color appearance characteristic of a printing media depends, and
converting an image composed of R, G, and B signals to a set of Y, M,
and C complementary-color images, each image being converted using one of
the plurality of gamma data;
means for selecting a best of the set of Y, M, and C complementary color
images; and
means for adjusting a printing process of the printer with the gamma data
used to convert the selected best Y, M, and C complementary color image.

2. (Amended) The printer as set forth in claim 1, wherein the table
comprises a memory means in which there is stored the plurality of gamma data
different from each other in gamma value upon which the color appearance
characteristic of the printing medium depends.

3. (Amended) The printer as set forth in claim 2, wherein the image
processing means calculates the plurality of gamma data with reference to a
reference image and changes the addresses of the data in the memory means.

4. (Amended) The printer as set forth in claim 1, wherein the image
processing means has a complementary color converter in which the R, G, and
B image is converted to the set of Y, M, and C complementary-color images
being in the complementary relation with the R, G, and B image.

3
(continued)

5. (Amended) The printer as set forth in claim 4, wherein the conversion to the Y, M, and C complementary-color images for a desired number of frames is effected by an image dividing means which divides the Y, M, and C complementary-color images by a hardware capability of the image processor in a main scanning direction and by a software capability of the image processor in a sub scanning direction to generate Y, M, and C images for a number of columns for display of the frames.

6. (Amended) The printer as set forth in claim 1, wherein:
the table is a memory means in which there is stored the plurality of data different from each other to a gamma value upon which the color appearance characteristic of the printing medium depends, and a complementary color converter in which the R, G, and B image is converted to Y, M, and C images being in a complementary relation with the R, G, and B image; and
the image processor includes means for determining a number of frames for output of the Y, M, and C complementary-color images using the plurality of data.

7. (Amended) The printer as set forth in claim 6, wherein the conversion to the Y, M, and C complementary-color images for the number of frames is effected by an image dividing means which divides the Y, M, and C complementary-color images by the hardware in a main scanning direction and by the software in a sub scanning direction to generate Y, M, and C images to determine a number of columns to be used to output the frames.

8. (Amended) The printer as set forth in claim 1, wherein the printer includes a sublimation ink ribbon and the media includes printing paper.

9. (Amended) A color adjusting method for use in a printer to print a video signal using printing media, the method comprising steps of:

storing a plurality of data different from each other in a value on which a color appearance characteristic of the printing media depends in an updateable table;

converting, using the video signal, an image composed of R, G, and B video signals based on the video signal to complementary-color images to be output in a number of columns;

printing the set of complementary-color images as an output from the converting step using the printing media;

selecting a desired one of the set of complementary-color images as printed on printing paper at the printing step; and

adjusting colors of an output image according to the image selected at the selecting step.

10. (Amended) The method as set forth in claim 9, wherein at the step of storing, the plurality of data different from each other are gamma values upon which the color appearance characteristic of the printing media depends is stored.

11. (Amended) The method as set forth in claim 10, further comprising the step of updating the table with a set of gamma values based on a reference image.

12. (Amended) The method as set forth in claim 9, wherein at the converting step, the R, G, and B images are converted to Y, M, and C images being in the complementary relation with the R, G, and B images and further to Y, M, and C complementary-color images for a desired number of columns based on capabilities of an image processor performing the conversion.

13. (Amended) The method as set forth in claim 12, wherein the conversion to the Y, M, and C complementary-color images for the desired number of columns is effected by dividing the Y, M, and C complementary-color images by a hardware capability of the image processor in a main scanning direction and by a software capability of the image processor in a sub scanning direction to generate Y, M, and C images for the desired number of columns.

14. (Amended) The method as set forth in claim 9, wherein the plurality of data are different from each other in gamma value upon which the color appearance characteristic of the printing media depends, and the R, G, and B are converted to Y, M, and C images being in the complementary relation with the R, G, and B image and further to Y, M, and C complementary-color images in a desired number of frames using the plurality of data.

15. (Amended) The method as set forth in claim 14, wherein the conversion to the Y, M, and C complementary-color images for the desired number of frames is effected by dividing the Y, M, and C complementary-color images by a hardware capability of the image processor in a main scanning direction and by a software capability of the image processor in a sub scanning direction to generate Y, M, and C images for a number of columns in which the converted images are to be output.

16. (Amended) The method as set forth in claim 9, wherein the printing media includes a sublimation ink ribbon and printing paper.

17. (Amended) The method as set forth in claim 9, wherein at the selecting step, the desired image is selected by prompting the user to select

one of positions on a monitor screen each position corresponding to one of the plurality of images printed on the printing paper.

18. (New) The printer according to claim 1, wherein said means for selecting comprises:

means for printing the set of Y, M and C complementary-color images in a test pattern;

means for outputting a selection pattern having a set of markers, each marker respectively corresponding to one of the test pattern images; and

means for identifying one of the markers corresponding to a best one of the test pattern images.

19. (New) The printer according to claim 18, further comprising means for updating the updateable table based on a reference image.

20. (New) The printer according to claim 19, wherein the table is updated by acquiring gamma data by calculation and storing each gamma data at addresses in the table.

21. (New) The printer according to claim 20, wherein:
the test pattern images are printed by updating a gamma value used for each line printed by changing an address that reads a corresponding gamma data from the table;

the address is changed in a sub-scanning direction by software; and
the address is changed in a main-scanning direction by hardware.

22. (New) A method comprising the steps of:
storing a plurality of data different from each other in a value on which a color appearance characteristic of a printout depends;

selecting, by a user, an important area of a subject image;
creating a plurality of test images, each test image being created by
applying an individual one of the data to the important area of the subject
image;
printing the test images;
outputting a set of markers, each marker corresponding to one of the
printed test images, on a display screen;
retrieving a user selection of the markers; and
applying the data used to create the test image corresponding to the
selected marker to a printing operation.

23. The method according to claim 22, wherein said step of applying the
data comprises saving the data used to create the test image corresponding to
the selected marker in a printer.

24. The method according to claim 23, wherein said step of storing
comprises storing gamma data.

25. The method according to claim 23, wherein said step of storing
comprises storing the data in an updateable table.

26. The method according to claim 23, wherein said step of storing
comprises storing gamma data based on the subject image in an updateable
table.